

Vehicle Folder: 2013 ford expedition  
 Date: 29-Apr-2019  
 Time: 09:32:29  
 Run ID: stock exped  
 Run No: 1

Correction Method: SAE

Run Comment:

Vehicle Specification  
 Wheel Diameter (mm): 600.0  
 Weight (Kg): 1400.00  
 Drive Ratio: 6.26500000  
 Trans.C. Factor: 1.000000  
 Gearbox: MANUAL  
 Gear: 4  
 Control Mode: CUSTOM



EngRPM	Torque lbft	Power HP	Temp °F	MAP PSI	Lambda	AFR	PCRatio P/PC	Time sec	Baro InHc	T.Effort lb
4100	284.821	222.343	65.9	-0.27	0.00	0.00	1.04399	3.306	28.822	1812.96
4200	276.970	221.487	65.9	-0.26	0.00	0.03	1.04404	3.582	28.822	1762.98
4300	276.258	226.178	65.9	-0.27	0.00	0.00	1.04403	3.822	28.822	1758.45
4400	277.393	232.388	65.9	-0.29	0.00	0.06	1.04403	4.082	28.822	1765.67
4500	278.192	238.354	65.9	-0.27	0.00	0.06	1.04403	4.294	28.822	1770.76
4600	282.335	247.280	65.9	-0.28	0.01	0.12	1.04404	4.556	28.822	1797.13
4700	284.693	254.763	65.9	-0.28	0.00	0.03	1.04406	4.836	28.822	1812.14
4800	283.286	258.900	65.9	-0.25	0.00	0.00	1.04408	5.123	28.822	1803.18
4900	277.860	259.232	65.9	-0.30	0.00	0.04	1.04403	5.437	28.822	1768.64
5000	272.881	259.793	65.8	-0.29	0.00	0.00	1.04402	5.694	28.821	1736.95
5100	269.651	261.842	65.9	-0.27	0.00	0.06	1.04410	5.955	28.821	1716.39
5200	268.248	265.586	65.9	-0.24	0.00	0.00	1.04409	6.279	28.821	1707.46

Vehicle Folder: 2013 ford expedition  
 Date: 30-Apr-2019  
 Time: 11:01:35  
 Run ID: perf 3in  
 Run No: 1

Correction Method: SAE

Run Comment:

Vehicle Specification  
 Wheel Diameter (mm): 600.0  
 Weight (Kg): 1400.00  
 Drive Ratio: 6.26500000  
 Trans.C. Factor: 1.000000  
 Gearbox: MANUAL  
 Gear: 4  
 Control Mode: CUSTOM



EngRPM	Torque lbft	Power HP	Temp °F	MAP PSI	Lambda	AFR	PCRatio P/FC	Time sec	Baro InHg	T.Effort lb
4100	288.103	224.905	65.2	-0.11	0.00	0.06	1.03258	3.535	29.123	1833.85
4200	289.498	231.505	65.3	-0.15	0.00	0.00	1.03263	3.842	29.123	1842.72
4300	285.802	234.013	65.2	-0.13	0.00	0.00	1.03253	4.233	29.124	1819.20
4400	282.053	236.292	65.2	-0.13	0.00	0.02	1.03254	4.614	29.124	1795.33
4500	274.979	235.601	65.2	-0.11	0.00	0.00	1.03249	4.999	29.125	1750.30
4600	271.730	237.992	65.2	-0.11	0.01	0.11	1.03248	5.318	29.124	1729.63
4700	270.511	242.075	65.2	-0.08	0.01	0.09	1.03253	5.629	29.124	1721.87
4800	270.735	247.430	65.2	-0.12	0.01	0.07	1.03248	5.892	29.125	1723.29
4900	273.692	255.343	65.2	-0.10	0.01	0.13	1.03251	6.140	29.125	1742.11
5000	277.132	263.830	65.2	-0.13	0.00	0.00	1.03247	6.481	29.125	1764.01
5100	274.803	266.845	65.2	-0.10	0.00	0.00	1.03247	6.903	29.124	1749.19
5200	272.807	270.101	65.1	-0.09	0.01	0.08	1.03244	7.307	29.124	1736.48